



# TRACTOREXPORT.COM

	Model	Hours	Price
John Deere	7200R	1711	\$ 149,859
	7200R	1522	\$ 140,778
	7200R	1092	\$ 151,922
	7200R	796	\$ 151,922
	7200R	782	\$ 151,922
	7200R	801	\$ 151,922
	7200R	461	\$ 151,922

ENGINE	
<b>Make</b>	John Deere PowerTech PSX turbocharged aftercooled diesel
<b>Model</b>	7200R
<b>Peak rated power</b>	200 hp
<b>Number of cylinders</b>	6
<b>Displacement</b>	6.8L 414 cu in.
<b>Alternator</b>	200 amp
<b>Bore/Stroke</b>	4.19x5.00 inches [106 x 127 mm]
<b>Emissions</b>	Tier 4A
<b>Emission control</b>	exhaust gas recirculation (EGR)
<b>Rated Power (EC 97/98)</b>	200 hp [149.1 kW]
<b>Maximum Power (EC 97/68)</b>	220 hp [164.1 kW]
<b>Fuel system</b>	electronic high-pressure common rail
<b>Air cleaner</b>	dual stage dry
<b>Compression</b>	17 2 1
<b>Rated RPM</b>	2100
<b>Starter</b>	electric
<b>Starter volts</b>	12

<b>TRANSMISSION</b>	
<b>Transmission</b>	PowerQuad Plus
<b>Type</b>	partial power shift
<b>Gears</b>	16 forward and reverse
Four gears (1-4) in four ranges (A-D) with left-hand reverser lever. Push-button power shifting between gears. Synchronized shifting between ranges using the foot clutch, or de-clutch button. Power shuttle shifting between forward and reverse	

<b>3-POINT HITCH</b>	
<b>Rear Type</b>	3/3N
<b>Control</b>	electro-hydraulic sensing
<b>Rear lift</b>	12,000 lbs [5443 kg]
<b>Front Hitch</b>	3N (optional)
<b>Front lift</b>	11,463 lbs [5200 kg]

<b>POWER TAKE-OFF (PTO)</b>	
<b>Rear PTO</b>	Independent
<b>Rear RPM</b>	1000 (1.75) 540/1000 (1.375/1.75) 540/540E/1000 (1.375/1.75) 540/540E/1000/1000E (1.375/1.75)
<b>Engine RPM</b>	540@1950 540E@1750 1000@1950 1000E@1950
<b>Front PTO</b>	Optional
<b>Front RPM</b>	1000 (1.375) 1000 (1.75)

<b>MECHANICAL</b>	
<b>Chassis</b>	4x2 2WD (optional) 4x4 MFWD 4WD
<b>Differential lock</b>	full-locking electrohydraulic rear. Limited slip 4WD front axle. Electrohydraulic on TLS Plus front axle with front brakes.
<b>Steering</b>	hydrostatic power ActiveCommand Steering optional
<b>Cab</b>	Command View II Cab. Auto Trac ready, except on 2WD. ISO 1178.3 ISOBUS connection. JD Link and Service ADVISOR Remote available.

<b>DIMENSIONS</b>	
<b>2WD Weight</b>	18,104 lbs [8211 kg]
<b>4WD Weight</b>	23,080 lbs [10469 kg]

<b>Weight (max capacity)</b>	31,967 lbs [14500 kg]
<b>Front axle load</b>	14,330 lbs [6500 kg]
<b>Rear axle load</b>	23,149 lbs [10500 kg]
<b>2WD Wheelbase</b>	119.4 inches [303 cm]
<b>4WD Wheelbase</b>	115.2 inches [292 cm]
<b>Front axle</b>	1150 Series standard Triple-Link Suspension Plus optional 2WD optional inch diameter [50 mm]
<b>Rear axle</b>	Standard axle 3.94 by 118.5 inches [100x3009 mm] 3.94 by 100.4 inches [100x2550 mm] 3.94 by 110.5 inches [100x2806 mm]
<b>Front tread</b>	60 to 88 inches [152 to 223 cm]
<b>TLS Plus Weight</b>	26,335 lbs [11945 kg]

