

	Model	Hours	Price
John Deere	9360R	3034	\$ 218,094
	9360R	2091	\$ 251,400

ENGINE	
Make	John Deere Power Tech PSX turbocharged
	diesel
Model	9360R
Peak rated power	360 hp
Number of cylinders	6
Displacement	9.0L 549.2 cu in.
Bore/Stroke	4.661x5.354 inches [118 x 136 mm]
Emissions	Tier 4A
Emission control	exhaust gas recirculation (EGR)
Rated Power (EC 97/98)	360 hp [268.5 kW]
Maximum Power (EC 97/68)	396 hp [295.3 kW]
Fuel system	electronic high-pressure common rail
Compression	16:1
Rated RPM	2100
Starter volts	12

TRANSMISSION		
Transmission	John Deere PowrSync	
Туре	partial power shift	
Gears	24 forward and 4 reverse	
Clutch	Hydraulic wet disc	
Three gears (1-3) in four ranges (A-D) with high-low power shift. Synchronized shifting between gears and ranges.		

3-POINT HITCH		
Rear Type	4N/3	
	4N/4	

Control	electronic draft sensing
Rear lift	15,300 lbs [6940 kg]
	20,000 lbs [9072 kg](optional)

POWER TAKE-OFF (PTO)	
Rear PTO	Independent (optional)
Rear RPM	1000 (1.75)
Drawbar	Category 4 standard with optional heavy- duty support (2,470 kg). Optional Category 5 with heavy-duty support rated at 5,440 kg.

MECHANICAL	
Chassis	4x4 articulated 4WD
Final drives	inboard planetary
Differential lock	fully-locking electro-hydraulic
Steering	hydraulic power
Brakes	hydraulic wet disc
Trailer brakes	hydraulic optional
Cab	Command View II cab standard with air-
	conditioning.

HYDRAULICS	
Туре	closed center pressure flow compensated
Pressure	2900 psi [200.0 bar]
Valves	4 to 6
Pump flow	44 gpm [166.5 lpm]
	48 gpm [181.7 lpm] (PowerShift)
	78 gpm [295.2 lpm] (High-Flow)
SCV flow	37 gpm [140.0 lpm]
	45 gpm [170.3 lpm] (19.1mm SCV)

DIMENSSIONS	
Weight (shipping)	34420 lbs [15612 kg]
Weight (operating)	37705 lbs [17102 kg] (480/80R46 duals)
Wheelbase	137.8 inches [350 cm]
Length	282 inches [716 cm]
With hitch Length	295 inches [749 cm]
Width	120 inches [304 cm]
Height (hood)	106 inches [269 cm]
Height (cab)	143 inches [363 cm]
	149 inches [378 cm] (GPS)
Height (exhaust)	175 inches [444 cm]
Front axle	4.33 by 120 inches [109x3048 mm]
	4.72 by 120 inches [119x3048 mm] (optional)

Rear axle	4.33 by 120 inches [109x3048 mm] 4.72 by 120 inches [119x3048 mm] (optional)
Ag front	620/70R42
Ag rear	620/70R42

