

|               | Model | Hours | Price         |
|---------------|-------|-------|---------------|
| John<br>Deere | 9430  | 5122  | \$<br>215,465 |
| 2 3 3 3       | 9430  | 4641  | \$<br>213,809 |

| ENGINE              |  |
|---------------------|--|
| Make                | John Deere turbocharged aftercooled diesel |
| Model               | 9430                                       |
| Peak rated power    | 425 hp                                     |
| Number of cylinders | 6  |
| Displacement        | 13.5L 826.7 cu in.                         |
| Bore/Stroke         | 5.197x6.496 inches [132 x 165 mm]          |
| Power               | 425 hp [316.9 kW]                          |
| Air cleaner         | aspirator and dual paper elements          |
| Compression         | 16.0 1                                     |
| Rated RPM           | 2100                                       |
| Starter volts       | 12   |
| Oil capacity        | 44 qts [41.6 L]                            |
| Coolant capacity    | 70 qts [66.2 L]                            |

| TRANSMISSION  |                          |  |
|---|--------------------------|--|
| Transmission  | John Deere PowrSync      |  |
| Туре  | partial power shift      |  |
| Gears   | 24 forward and 4 reverse |  |
| Clutch  | Hydraulic wet disc       |  |
| Three gears (1-3) in four ranges (A-D) with high-low power shift. Gears and range shifts are synchronized using the clutch. |                          |  |

| 3-POINT HITCH |      |  |
|---------------|------|--|
| Rear Type     | 4N/3 |  |
|               | 4N/4 |  |

| <b>Rear lift (at 24"/610mm)</b> 15,300 lbs [6] | 940 kg] |
|--|---------|
|--|---------|

| POWER TAKE-OFF (PTO) |   |
|----------------------|---|
| Rear PTO             | Independent (optional)  |
| Rear RPM             | 1000 (1.75)   |
| Clutch               | electro-hydraulic wet disc  |
| Drawbar              | Catergory 4 standard with secondary chain support. Optional reinforcement up to 11,000 pounds. Optional 12,000 pounds Catergory 5 drawbar, not available with 3-point hitch or PTO. |

| MECHANICAL        |  |
|-------------------|--|
| Chassis           | 4x4 articulated 4WD                      |
| Differential lock | hydraulic differential lock optional     |
| Steering          | hydrostatic power                        |
| Brakes            | hydraulic wet discs                      |
| Trailer brakes    | hydraulic optional                       |
| Cab               | Command View Cab standard with air-      |
|                   | conditioning. Optional automatic climate |
|                   | control and leather trim                 |

| HYDRAULICS            |  |
|-----------------------|--|
| Туре                  | closed center pressure flow compensated  |
| Capacity              | 27 gal [102.2 L]                         |
|                       | 28 gal [106.0 L] (3-point)               |
|                       | 20 gal [75.7 L] (high-flow)              |
|                       | 31 gal [117.3 L] (high-flow and 3-point) |
| Pressure              | 2900 psi [200.0 bar]                     |
| Valves                | 4 to 6                                   |
| SCV flow              | 30 gpm [113.6 lpm]                       |
| PowrSync Total flow   | 44 gpm [166.5 lpm]                       |
| PowerShift Total flow | 48 gpm [181.7 lpm]                       |
| Hi-Flow Total flow    | 78 gpm [295.2 lpm]                       |

| DIMENSSIONS                |   |
|----------------------------|---|
| Weight (shipping)          | 35,530 lbs [16116 kg]                     |
| Weight (operating)         | 38,600 lbs [17508 kg] (480/80R46 triples) |
| Length                     | 270 inches [685 cm]                       |
|                            | 285 inches [723 cm] (with 3-point)        |
| Width                      | 118.6 inches [301 cm]                     |
| Height (hood)              | 107 inches [271 cm]                       |
| Height (cab)               | 142 inches [360 cm]                       |
| Height (exhaust)           | 156 inches [396 cm]                       |
| Hinge pin Ground clearance | 20.5 inches [52 cm]                       |

| Clearance (rear axle) | 30.8 inches [78 cm]               |  |
|-----------------------|-----------------------------------|--|
| Rear axle             | 4.331 by 120 inches [110x3048 mm] |  |

P-430
P-430